

Product Information

OBRA molecular sieve 10Å

Date: 07 / 2020

PI-No.: SIO-07 Revision: 00

page 1 of 1

Product Description

OBRA molecular sieve 10Å is a crystalline, high porous sodium alumino silicate. Gas, steams and liquids can be adsorbed reversibly or separated selectively due to the special crystal lattice with absolutely uniform, spherical cavities which are connected by channels. The large internal surface of 600 - 700 m²/g results in a strong bond of adsorption and in a polar characteristics of the molecular sieve structure. The pore openings are approx. 10Å across. Molecules bigger than the pore opening of the molecular sieve cannot be adsorbed smaller can.



Formela CAS-No.

 $Na_{86}[(AlO_2)_{86}(SiO_2)_{106}] \cdot H_2O$ 1318 - 02 - 1

Physico-chemical Characteristics

Adsorption capacity (on dry basis; 40 % RH, 23 °C) Moisture loss (1h, 550°C)

Bulk density compacted

min. 21 % max. 2.5 %

min. 650 g/l

Particle size

1,6 – 2,5 mm

Applications

OBRA molecular sieve 10Å is used in various applications, such as the purification of gas, the drying of steam and liquids and the removal

of CO₂ and water from air.

Packing

Airtight Steel drums or Big Bags

Note

Any details of application possibilities do not free the purchaser from the obligation of performing his own tests on the material supplied by the seller, in order to determine their suitability for the intended processes and purposes. Application, use and processing of the material cannot be controlled by the seller and are thus the sole responsibility of the purchaser

OKER-CHEMIE GmbH

© OKER-CHEMIE GmbH