

Product Information

OBRA Molecular sieve 4Å

Doc: PI-SIO-10

Date: 08 / 2025

Revision: 04



OBRA Molecular sieve 4Å

is a crystalline, highly porous sodium aluminosilicate. Gas, vapours and liquids can be adsorbed reversibly or separated selectively due to the special crystal lattice with absolutely uniform, spherical cavities which are connected by channels. The large internal surface area of 600 – 700 m²/g and the polar characteristics of the molecular sieve structure result in a strong bond of adsorption. The pore openings are approx. 4Å across – larger molecules cannot be adsorbed while smaller molecules are.

OBRA Molecular sieve 4Å

is used in various applications, such as the purification of gas, the drying of steam and liquids and the removal of CO_2 and water from air. The reactivation of OBRA molecular sieve 4Å takes place via heating up on 350 – 400 °C or via pressure reduction.

Basis			
Formula	Na ₁₂ [(AlO ₂) ₁₂ (SiO ₂) ₁₂] · 12 H ₂ O	CAS-No.	1318 – 02 – 1
Characteristics			
Adsorption capaciy at 10% rel.Humidity	min. 17.5 %	Moisture loss (1h, 550°C)	max. 3.0 %
Bulk density	min. 720 g/l	Grain size	1.0 – 2.0 mm 1.6 – 2.5 mm on request
Packaging			
Cardboard box	with polyethylene bags at 25 kg		
Steel drum	with polyethylene bags at 125 kg		

Note

Any details of application possibilities do not free the purchaser from the obligation of performing their own tests on the material supplied by the seller, in order to determine their suitability for the intended processes and purposes. Application, use and processing of the material cannot be controlled by the seller and are thus the sole responsibility of the purchaser.

OBRA molecular sieve 4Å must always be kept in airtight containers to avoid adsorption with water vapour. Face masks should be used at continual exposure to extensive dusting.